



INGLESE 65th

since 1956

www.inglesesrl.com

INGLESE LP650 PARTS CLEANER

**ink fountains, doctor blades and rollers
with motorized rotating basket Ø 700 mm**



COMPLIANT TO DIRECTIVES: 2006/42/CE - 2014/34/UE (ATEX)

- Fully pneumatic operation.
- Manufactured in AISI 304 stainless steel.
- PTFE double membrane pneumatic pump ATEX 2G.
- In and out filtering of cleaner.
- Three-way valve on pump sending for dirty solvent transfer to a collection tank.
- Sliding lid closing.
- Safety microswitch sealing on the lid.



INGLESE 65th

since 1956

www.inglesesrl.com

INGLESE LP650



- N. 1 external washing bar, upper and central.
N. 1 external and internal washing bar.
N. 1 external, internal and upper drying bar.
 - Washing useful height 700 mm.
 - Pneumatic pump sound proofing.
 - Venturi pneumatic suction.
 - Tank capacity recirculation Lt. 50:
the cleaning product is contained and recirculates in the side tank, inside the washing machine there is not any cleaning product, this eliminates the emission of vapors.
- Pneumatic motor for the basket rotation containing the pieces.
 - Pneumatic programmable logic:
 - 1° pneumatic timer -> washing.
 - 2° pneumatic timer -> pause.
 - 3° pneumatic timer -> suction and drying.

When the cleaning product is saturated, it is possible to transfer it by the pump avoiding manual processing.

To facilitate the load and unload of the parts, being the basket pneumatic motorized and with an irreversible reducer (it is not possible to manually rotate the basket) , the machine is equipped with a selector to facilitate the rotation of the basket outside the washing cycle.

Width: 1010 mm

Depth: 1520 mm

Height : 1350 mm

Weight: 310 Kg (without cleaning product)

Working pressure: 6-7 bar

Compressed air pipe: Ø 12 mm